

BROOKVENT

airvent

SM Tip Vent

Dimensions

(width x height x depth)



Regulator SM Tip Vent: 430 x 21 x 23 [mm]




Intake SM Tip Vent: 430 x 21 x 23 [mm]




GPE2A flat grill (option): 390 x 20 x 3 [mm]

Example installation

PVC window



Wooden window



Suitable for all types of window frame construction

Installation

As a standard, the SM Tip Vents are screwed to the joinery. For installation in windows with exterior blinds, use the GPE2A flat grid.

Notch size:



* specifications for notch size 12 mm

Air flow

Vent	10 Pa	20 Pa
SM Tip Vent	30 m ³ /h	40 m ³ /h

Instructions for designer.

Negative pressure of 20 Pa should be assumed for calculations of fresh air intake for mechanical extraction ventilation systems.

Acoustic insulation

Vent	Dn, e, w (C; Ctr)	Dn, e, A2*
SM Tip Vent	32 (0; 0) dB	32 dB

* Dn, e, A2: indicator of insulating a noise which is dominated by low tones such as city street traffic, discotheque music, slow speed rail traffic and far away jet planes

BROOKVENT Polska Sp. z o.o.

ul. Kościuszki 14-16
55 - 120 Oborniki Śląskie
woj. dolnośląskie

T +48 71 3105282

F +48 71 7503622

E informacja@brookvent.pl

www.brookvent.pl



air window ventilation range